



FOX 1

Piazzetta  design

# FOX 1

Gas or wood-burning fireplace with handmade majolica surround.

SURROUND WEIGHT: 115 kg

GAS BURNING (NATURAL GAS OR LPG) IG 90

FIREBOX: in Aluker®

INLET: in grey enamelled steel

GLASS: ceramic heat resistant up to 750°C

FUNCTION CONTROL: remote control

CERAMIC LOGS: standard supply

HEATING: convection and radiation

FLUE GAS OUTLET: concentric pipe Ø 10/15 cm

FIREBOX HEAT OUTPUT: 9,5 kW (Natural gas)  
9,5 kW (LPG)

THERMAL EFFICIENCY: 80% (Natural gas)  
75% (LPG)

CONSUMPTION AT RATED HEAT OUTPUT:  
0,90 m<sup>3</sup>/h (Natural gas)  
720 g/h (LPG)

WEIGHT: 90 kg

RATED HEAT OUTPUT: 6,8 kW (Natural gas)  
6,4 kW (LPG)

TYPE-EXAMINATION: EC certification E0780

OPTIONAL ACCESSORIES:

- river pebles
- height regulation kit

WOOD BURNING ME 90/44

INLET: in enamelled steel

FIREBOX: in Aluker®

GRATE: in Aluker® with cast iron grid

DOOR: rise n'fall with glass ceramic heat resistant up to 750°C, may also be opened as hinged door for cleaning

PRIMARY AIR: adjustable by hand

SECONDARY AIR: pre-determined

SMOKE DAMPER: automatic and adjustable

ASH DRAWER: removable

HEATING: natural convection

or forced air circulation by Multifuoco System® on request, with 1 or 2 ventilators.

FLUE OUTLET: Ø 25 cm

NOMINAL OUTPUT: 13,5 kW

THERMAL EFFICIENCY: 78,5 %

NOMINAL CONSUMPTION : 4 kg/h

MAX OUTPUT : 14,6 kW

MAX CONSUMPTION : 4,6 kg/h

WEIGHT: 285 kg

Laboratory measurements were made using beech wood with moisture content below 20%  
Type approval in accordance with EN13229

OPTIONAL ACCESSORIES:

- ventilation kit Multifuoco System® with automatic or manual switching on and off and 4-speed remote control.
- sensor kit for dual Multifuoco System®
- adjustable height kit

DIMENSIONI:

	IG90	ME90/44
A	24	43
B	93	95,5
C	12,5	19,5
Ø	15	25

Measurements expressed in cm

